# ALABAMA DEPARTMENT OF PUBLIC HEALTH

The RSA Tower, 201 Monroe Street, P.O. Box 303017, Montgomery, AL 36130-3017 (334) 206-5300 • FAX (334) 206-5534 Web Site: http://www.adph.org

### **NEWS RELEASE**

Be aware of the risk of chain saw injury during tree removal

	<i>5</i> • •	
FOR IMMEDIATE RELEASE	CONTACT:	Contact name (xxx) xxx - xxxx e-mail address
Each year, approximately	(number)	people are treated in hospital
emergency departments for injuries fron	n using chain saws.	, according to the Centers for
Disease Control and Prevention. The po	tential risk of injur	y increases after hurricanes
and other natural disasters, when chain s	saws are widely use	ed to remove fallen or partially
fallen trees and tree branches.		
"Before using a chain saw, be su	re you know how t	o operate it," said
(spokesperson) Alabama	a Department of Pu	blic Health. "Read and
understand the operator's manual and ob-	oserve an experienc	ced operator in action before
starting work."		
The CDC advises the public to follo	w these safeguards	against injury while using a

The CDC advises the public to follow these safeguards against injury while using a chain saw:

- Operate, adjust and maintain the saw according to manufacturer's instructions
  provided in the manual accompanying the chain saw.
- Properly sharpen chain saw blades and properly lubricate the blade with bar and chain oil. Additionally, the operator should periodically check and adjust the tension of the chain saw blade to ensure good cutting action.
- Choose the proper size of chain saw to match the job, and include safety features such as a chain brake, front and rear hand guards, stop switch, chain catcher and a spark arrester.
- Wear the appropriate protective equipment, including hard hat, safety glasses, hearing protection, heavy work gloves, cut-resistant leg wear (chain saw chaps) that extend from the waist to the top of the foot, and boots which cover the ankle.

- Avoid contact with power lines until the lines are verified as being de-energized.
- Always cut at waist level or below to ensure that you maintain secure control over the chain saw.
- Bystanders or coworkers should remain at least two tree lengths (at least 150 feet) away from anyone felling a tree and at least 30 feet from anyone operating a chain saw to remove limbs or cut a fallen tree.
- If injury occurs, apply direct pressure over site(s) of heavy bleeding; this act may save lives.

#### Beware of injury from the release of bent trees or branches

Take extra care in cutting "spring poles," trees or branches that have gotten bent, twisted, hung up on, or caught under another object during a high wind. If the tree or the branch is suddenly released, it may strike the person cutting it, or a bystander, with enough force to cause serious injury or death. Even a seemingly small tree or branch (2 inches in diameter, for example) may pose a hazard when it is released from tension.

## To avoid injury:

- Identify the maximum point of tension on the spring pole
- Slowly shave the underside of the tree rather than cut through to allow the tree or branch to release tension slowly

#### How the public can help

- It is best to have a chain saw operator who has training and experience in safe chain saw use and cutting techniques to fell and remove limbs from trees.
- Be sure that bystanders are at a safe distance from cutting activities, the chain saw operator uses personal protective equipment, and workers follow safety guidelines.